



ELITE FLEXIBLE DUCTING

COMMERCIAL EH – TYPE CP



CEH SERIES – TYPE CP

- CAN/ULC-S110 Listed
- Class 1 Air Duct
- Owens Corning Insulation is GREENGUARD Gold Certified
- SCS Certified (Min 57% Recycled Content)
- High Pressure Rated
- Maximum Rated Velocity
- Reinforced Trilaminare Core
- R-Value Options: 4.2; 6.0; 8.0
- Rugged Polyethylene Vapour Barrier
- No Adhesives used in Manufacturing Process
- Air Tight & Leak Proof
- Meets NFPA 90A & 90B; ASTM Standards



TECHNICAL DATA:

Underwriters Laboratories of Canada Listed	CAN/ULC-S110 Listed - Air Duct
ULC Classification	Class 1
Flame Spread Rating/Smoke Developed Rating	< 25/50
Maximum positive pressure	3 kPa (12 in. wc)
Maximum negative pressure	0.25 kPa (1 in. wc)
Maximum rated velocity	20.3 m/s (4000 fpm)
Available sizes	50mm to 600mm (02" to 24")
Operating temperature	-20°F to +250°F
Fiberglass Insulation	Greenguard Gold Certified



SUGGESTED SPECIFICATION:

Insulated flexible ducting shall be CEH-CP by Peppertree Air Solutions Inc. The core is constructed of a high tensile reinforced trilaminare mechanically locked to an external steel helix; wrapped in Owens Corning GREENGUARD Gold Certified FIBERGLAS® insulation; and sleeved with a flame retardant polyethylene vapour barrier. CEH-CP is ULC-S110 Listed as a Class 1 Air Duct with a Flame Spread Rating of not over 25 without evidence of continued progressive combustion and a Smoke Developed Rating of not over 50 in accordance with the “National Building Code of Canada.”

The Listing Mark of Underwriters Laboratories of Canada on the product is the only method by ULC to identify products manufactured under its Listing and Follow-Up-Service. The Listing Mark for these products includes the ULC symbol together with the word “LISTED”, a control number, and the product name “Air Duct.”