



ELITE FLEXIBLE DUCTING

COMMERCIAL EH – TYPE D



CEH SERIES – TYPE D

- CAN/ULC-S110 Listed
- Class 1 Air Duct Material
- Maximum Rated Velocity
- High Pressure Rated
- Vinyl-Coated Fiberglass Cloth
- Exterior Galvanized Steel Helix
- No Glues or Adhesives
- Excellent Bend Radius
- Extremely Resilient Material
- Air Tight & Leak Proof
- Available in Wide Range of Sizes
- Meets NFPA 90A & 90B; ASTM Standards
- Manufactured in Standard 25ft Lengths



TECHNICAL DATA:

Underwriters Laboratories of Canada Listed	CAN/ULC-S110 Listed - Air Duct
ULC Classification	Class 1
Flame Spread Rating/Smoke Developed Rating	< 25/50
Maximum positive pressure	3 kPa (12 in. wc)
Maximum negative pressure	0.13 kPa (.5 in. wc)
Maximum rated velocity	20.3 m/s (4000 fpm)
Available sizes	50mm to 600mm (02" to 24")
Operating temperature	-20°F to +250°F



SUGGESTED SPECIFICATION:

Non-insulated flexible ducting shall be CEH – Type D by Peppertree Air Solutions Inc. The product shall be manufactured from a strip of flame retardant vinyl-coated fiberglass cloth spirally wound and mechanically bonded to an exterior galvanized steel helix. No glues or adhesives are used in the fabrication of this product. CEH-D is ULC-S110 Listed as Class 1 Air Duct with a Flame Spread Rating of not over 25 without evidence of continued progressive combustion and a Smoke Developed Rating of not over 50 in accordance with the “National Building Code of Canada.”

The Listing Mark of Underwriters Laboratories of Canada on the product is the only method by ULC to identify products manufactured under its Listing and Follow-Up-Service. The Listing Mark for these products includes the ULC symbol together with the word “LISTED”, a control number, and the product name “Air Duct.”