



TRUE FLEX DUCT

COMMERCIAL TF2



TRUE FLEX (BARE) 2-PLY ALUMINUM DUCT- MODEL TF2

- Heavy Duty 2-ply Aluminum
- CAN/ULC-S110 Listed
- Class 1 Air Duct Connector
- High Pressure Rated
- Quality Triple-Seam
- Lightweight Aluminum
- Excellent Bend Radius
- Air-Tight & Leak-Proof
- Self-Supporting
- Compressed for Easy Handling
- Extremely Dependable
- Custom Length Fabrication



TECHNICAL INFORMATION:

Underwriters Laboratories of Canada Listed	CAN/ULC-S110 Listed - Air Duct Connector
ULC Classification	Class 1
Flame Spread Rating/Smoke Developed Rating	< 25/50
Maximum positive pressure	1.5 kPa (6 in. wc)
Maximum negative pressure	0.25 kPa (1 in. wc)
Maximum rated velocity	20.3 m/s (4000 fpm)
Available sizes	50mm to 600mm (02" to 24")
Operating temperature	-20°F to +250°F



SUGGESTED SPECIFICATION:

Aluminum flex duct shall be Commercial True Flex (Bare) – Model TF2 by Peppertree Air Solutions Inc. Flex duct shall be manufactured from 2 continuous strips of spirally wound aluminum, mechanically interlocked to produce an air-tight and leak proof seam. The 2-ply construction creates a stronger, tougher and more durable flexible duct for those special applications. TF2 is ULC-S110 Listed as a Class 1 Air Duct Connector with a Flame Spread Rating of not over 25 without evidence of continued progressive combustion and a Smoke Developed Rating of not over 50 in accordance with the “National Building Code of Canada.”