



# TRUE FLEX THERMAL DUCT

## COMMERCIAL TF – MODEL TFT-M



### TRUE FLEX (THERMAL) ALUMINUM DUCT – MODEL TFT-M

- Commercial Grade
- CAN/ULC-S110 Listed
- Class 1 Air Duct Connector
- Owens Corning Insulation is GREENGUARD Gold Certified and SCS Certified (Min 57% Recycled Content)
- Air Tight & Leak Proof
- Quality Triple-Seam
- R-Value Options: 4.2; 6.0; 8.0
- Metalized Vapour Barrier Reinforced with Fiberglass Scrim
- NFPA 90A & 90B - ASTM E84 Compliant



### TECHNICAL INFORMATION:

Underwriters Laboratories of Canada Listed	CAN/ULC-S110 Listed - Air Duct Connector
ULC Classification	Class 1
Flame Spread Rating/Smoke Developed Rating	< 25/50
Maximum positive pressure	1.5 kPa (6 in. WC)
Maximum negative pressure	0.25 kPa (1 in. WC)
Maximum rated velocity	20.3 m/s (4000 fpm)
Available sizes	50mm to 600mm (02" to 24")
Operating temperature	-20°F to +250°F (-29°C to +121°C)
Fiberglass Insulation	Greenguard Gold Certified



### SUGGESTED SPECIFICATION:

Insulated aluminum flex duct shall be Commercial True Flex – Model TFT-M by Peppertree Air Solutions Inc. The core shall consist of TF Basic; wrapped in Owens Corning GREENGUARD Gold Certified FIBERGLAS® insulation and sleeved with a reinforced metalized vapour barrier. TFT-M is a ULC-S110 Listed Class 1 Air Duct Connector with a Flame Spread Rating of not over 25 without evidence of continued progressive combustion and a Smoke Developed Rating of not over 50.

The Listing Mark of Underwriters Laboratories of Canada on the product is the only method by ULC to identify products manufactured under its Listing and Follow-Up-Service. The Listing Mark for these products includes the ULC symbol together with the word "LISTED", a control number, and the product name "Connector."