



TRUE FLEX DUCT

COMMERCIAL TF



TRUE FLEX (BARE) ALUMINUM DUCT– MODEL TF

- Commercial Grade
- CAN/ULC-S110 Listed
- Class 1 Air Duct Connector
- High Pressure Rated
- Quality Triple-Seam
- Lightweight Aluminum
- Excellent Bend Radius
- Air-Tight & Leak-Proof
- Self-Supporting
- Compressed for Easy Handling
- Extremely Dependable
- Custom Length Fabrication



TECHNICAL INFORMATION:

Underwriters Laboratories of Canada Listed	CAN/ULC-S110 Listed - Air Duct Connector
ULC Classification	Class 1
Flame Spread Rating/Smoke Developed Rating	< 25/50
Maximum positive pressure	1.5 kPa (6 in. WC)
Maximum negative pressure	0.25 kPa (1 in. WC)
Maximum rated velocity	20.3 m/s (4000 fpm)
Available sizes	50mm to 600mm (02" to 24")
Operating temperature	-20°F to +250°F



SUGGESTED SPECIFICATION:

Aluminum flex duct shall be Commercial (Bare) True Flex – Model TF by Peppertree Air Solutions Inc. Flex duct shall be manufactured from a continuous strip of spirally wound 3003 corrugated aluminum, mechanically interlocked to produce an air-tight and leak proof triple seam. TF (Bare) is ULC-S110 Listed as Class 1 Air Duct Connector with a Flame Spread Rating of not over 25 without evidence of continued progressive combustion and a Smoke Developed Rating of not over 50 in accordance with the "National Building Code of Canada."

The Listing Mark of Underwriters Laboratories of Canada on the product is the only method by ULC to identify products manufactured under its Listing and Follow-Up-Service. The Listing Mark for these products includes the ULC symbol together with the word "LISTED", a control number, and the product name "Connector."