MATERIAL SAFETY DATA SHEET

DP 2502 WATER BASED DUCT LINER ADHESIVE Page: 1

PRODUCT NAME: WATER BASED DUCT LINER ADHESIVE HMIS CODES: H F R P

PRODUCT CODE: DP 2502 1 0 0 B

MANUFACTURERS' NAME: DESIGN POLYMERICS

ADDRESS: 11609 MARTENS RIVER CIRCLE FOUNTAIN VALLEY, CA 92708

EMERGENCY PHONE: Chem-Tel: (800) 255-3924 (24 Hrs) BUSINESS HOURS: 7:30am – 4:30pm PT

INFORMATION PHONE: (714) 432-0600 REVISION DATE: February 18, 2010

REVISION #: 8

PREPARED BY: Technical Dept. Supersedes all previous

DOT Hazard Class Not Hazardous UN Number N/A Shipping Name N/A Packing Group N/A

======== SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION ==============

VAPOR PRESSURE WEIGHT

REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP PERCENT

None

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EYES: In direct contact, may cause irritation. SKIN: Prolonged and repeated contact with product may cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE: May cause irritation to skin and eyes, gastrointestinal irritation, nausea, and vomiting. CHRONIC: None known.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

INHALATION: If affected by inhalation, remove victim to fresh air. If symptoms persist, seek medical attention.

SKIN: Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water for at least 15 minutes. Wash contaminated clothing before reuse. If irritation persists, seek medical attention.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes while frequently lifting the upper and lower eyelids. If irritation persists, call a physician.

INGESTION: If swallowed, contact physician or emergency medical facility immediately to determine the best course of action.

FLASH POINT: Not Applicable METHOD USED: Not Applicable

FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: The product will only burn after the water it contains is driven off. For dried film use water, foam, carbon dioxide or dry chemical.

MATERIAL SAFETY DATA SHEET

DP 2502 WATER BASED DUCT LINER ADHESIVE

Page: 2

SPECIAL FIRE FIGHTING PROCEDURES: When dried film burns, carbon dioxide (CO₂), carbon monoxide (CO), and smoke are produced. Firefighters should wear self-contained breathing apparatus, especially in enclosed areas. Cool containers and minimize vapors with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high temperatures may burst due to build-up of steam pressure.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike, contain, or absorb with inert absorbent material. Collect spilled material in a salvage container. Prevent spill from entering sewers, drains, streams, waterways, or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

========== SECTION VII - PRECAUTIONS FOR SAFE HANDLING, STORAGE, AND USE ===========

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **DO NOT ALLOW TO FREEZE.** Store in a cool dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. Avoid inhalation of excess vapors, ingestion, and unnecessary, prolonged, or repeated contact with this and any other chemical. Change soiled work clothes frequently. Clean hands after handling. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: Not required under normal conditions. Provide sufficient ventilation to maintain constant fresh air in workspace. Avoid breathing sanding dust.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain constant fresh air in workplace.

SKIN PROTECTION (PROTECTIVE GLOVES): Resistant gloves such as polyethylene are recommended.

EYE PROTECTION: Use goggles or OSHA permitted safety glasses when splash potential exists.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious clothing. Eye wash station.

WORK / HYGENIC PRACTICES: Source of clean water should be available for flushing eyes and washing skin. Wash thoroughly after handling any chemicals, especially before eating, drinking, or smoking. Remove and launder contaminated clothing before reuse.

PHYSICAL FORM: Mobile Liquid

ODOR: Mild. sweet

SOLUBILITY IN WATER: Miscible

BOILING POINT: 212°F FREEZING POINT: 32° F (0° C)

COATING V.O.C.: 22 g/l

COLOR: White or Black

pH: 8.0-9.5

SPECIFIC GRAVITY (H₂O=1): 1.1-1.2 % VOLATILES BY WEIGHT: 55-65 VISCOSITY (cps): approx. 2,000-3,500

STABILITY: Stable at ambient temperatures.

CONDITIONS TO AVOID: Coagulation may occur after freezing, thawing, or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts, mineral acids (i.e. sulfuric, phosphoric, etc.) Strong oxidizing agents.

Strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials on thermal decomposition including Carbon monoxide (CO), Carbon dioxide (CO2), and various hydrocarbons.

MATERIAL SAFETY DATA SHEET

DP 2502 WATER BASED DUCT LINER ADHESIVE

This product is considered non-hazardous under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Section 311/312 Categorizations (40 CFR 370): Immediate (Acute) Health Hazard.

Section 313 Information (40 CFR 372) – Toxic Chemicals List: No components of this product are present in quantities above "deminimus" levels.

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CERCLA INFORMATION (40cfr 302.4): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): None listed.

-DISCLAIMER =======================
•

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.

Page: 3