## MATERIAL SAFETY DATA SHEET

DP 2540 BLACK, PROTECTIVE COATING Page: 1

PRODUCT NAME: BLACK, PROTECTIVE COATING HMIS CODES: H F R P

**PRODUCT CODE:** DP 2540 1 0 0 B

MANUFACTURERS' NAME: DESIGN POLYMERICS

ADDRESS: 11609 MARTENS RIVER CIRCLE FOUNTAIN VALLEY, CA 92708

EMERGENCY PHONE: Chem-Tel: (800) 255-3924 (24 Hrs) BUSINESS HOURS: 7:30am – 4:30pm PT

INFORMATION PHONE: (714) 432-0600 REVISION DATE: February 21, 2011

REVISION #: 6-1

PREPARED BY: Technical Dept. Supersedes all previous

======== SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION =============

REPORTABLE COMPONENTS

\* Barium Metaborate Monohydrate
TLV/TWA: 0.5 mg/m³

\* UAPOR PRESSURE
mm Hg @ TEMP
PERCENT

13701-59-2
N/A
N/A
5-10 %

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372.

PHYSICAL FORM: Mobile Liquid COLOR: Black

ODOR: Mild, sweet pH: 8.0-9.5

SOLUBILITY IN WATER: Miscible

SPECIFIC GRAVITY (H<sub>2</sub>O=1): 1.2-1.3

BOILING POINT: 212°F

W VOLATILES BY WEIGHT: 30-50 (Water)

VISCOSITY (cps): approx. 3,000-6,500

COATING V.O.C.: 2 g/l

FLASH POINT: Not Applicable METHOD USED: Not Applicable

FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: The product will only burn after the water it contains is driven off. For dried film use water, foam, carbon dioxide or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: When dried polymer burns, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO) and smoke are produced. Firefighters should wear self-contained breathing apparatus, especially in enclosed areas. Cool containers and minimize vapors with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high temperatures may explode or burst due to build-up of steam pressure.

STABILITY: Stable at ambient temperatures.

CONDITIONS TO AVOID: Coagulation may occur after freezing, thawing, or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts, mineral acids (i.e. sulfuric, phosphoric, etc.) Strong oxidizing agents. Strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials on thermal decomposition including Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), and various hydrocarbons. Contact with strongly acidic aqueous systems can release solubilized barium salts, which are highly toxic.

### MATERIAL SAFETY DATA SHEET

DP 2540 BLACK, PROTECTIVE COATING

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: EYES: In direct contact, may cause irritation. SKIN: Prolonged and repeated contact with product may cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE: May cause irritation to skin and eyes, gastrointestinal irritation, nausea, and vomiting. CHRONIC: Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike, contain, or absorb with inert absorbent material. Prevent spill from entering sewers, drains, streams, waterways, or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **DO NOT ALLOW TO FREEZE.** Store in a cool dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

OTHER PRECAUTIONS: DO OT TAKE INTERNALLY. Avoid unnecessary, prolonged, or repeated contact with this and any other chemical. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION: Not required under normal conditions. Provide sufficient ventilation to maintain constant fresh air in workspace. If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

SKIN PROTECTION (PROTECTIVE GLOVES): Wear resistant gloves such as polyethylene.

EYE PROTECTION: Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious clothing. Eye wash station.

WORK / HYGENIC PRACTICES: Source of clean water should be available for flushing eyes and washing skin. Wash thoroughly after handling any chemicals, especially before eating, drinking, or smoking. Remove and launder contaminated clothing before reuse.

#### **WORKPLACE CLASSIFICATIONS:**

This product is considered non-hazardous under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

This material is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

### TRANSPORTATION CLASSIFICATIONS:

U.S. DOT HAZARD CLASS: Non-Regulated.

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Page: 2

# MATERIAL SAFETY DATA SHEET

#### DP 2540 BLACK, PROTECTIVE COATING

Section 302 Categorizations - Extremely Hazardous Substances List: No components of this product are listed.

Section 311/312 Categorizations (40 CFR 370): Immediate (Acute) Health Hazard.

Section 313 Information (40 CFR 372) – Toxic Chemicals List: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

Component CAS# % by Weight Barium metaborate monohydrate 13701-59-2 5-10%

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CERCLA INFORMATION (40cfr 302.4): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): This product may contain trace amounts of chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.

Page: 3